



Rig 12- 5000m Cantilever Triple

Drawworks:	Superior 700E Modified	Well Control:	Wagner Five Station 90 Gallon
Engine:	GE 752	Annular:	Shaffer 11" 5K
Mast:	OCD Model 550	Pipe Rams:	Shaffer 11" 5K
Height:	142'	Manifold:	31/8" 5k
Max. Hook load:	244,650 daN	HCR:	Cammeron HCR
Substructure:	OCD Model 550	BOP:	
Max setback:	177,930 daN	Tubulars:	
Rotary/KB Beam to Ground:	5.63m	Collars:	18-165mm 4.5" DC
Clear Working Height:	4.97m	Drill Pipe:	340- 101.6mm 4" FH X-95
Pumps:	F-1000's	HWDP:	60-101.6mm 4" FH
Engine:	2- Cat C-27 , 1050 HP	Overhead:	
Mud System:	Twin tanks, 140m3	Top Drive:	Tesco 250 Ton HMI, 475 HP
Tank:		Hook/Block:	
Shakers:	Two DFTS dual deck Linear shakers	Drilling Line:	28.6mm
Pumps:	2- 6x5x11 Mission Magnum	Miscellaneous:	
Trip Tank:	3 m3	Water Tank:	Self raising Dog House, 55 m3
Pill tank:	5 m3	Fuel Tank:	TC-44 spec tank, 25,000l
Suction Tank:	35 m3	Boiler:	Cleaver Brooks 80 HP
Settling Tank 1:	35 m3	Features:	Hydraulic Skate Catwalk, Rig Smart Crown Saver, BOP handling system, rig leveling rams.
Settling Tank 2:	30 m3	Rig Loads:	
Shaker Tank:	30 m3	Rig:	26
Agitators:	4 SOS Euro drive	Boiler:	1
Gen Sets:	2 Stewart and Stevenson 475KW	Loader TP Shack & Misc.	3
Engine:	2- Cummins QFX15,675 HP	Racking Capability:	5000+m
Panel:	MCC, Allen Bradley PLC		