



Rig 18- 4000m Cantilever Triple

Drawworks:	Brewster N-45 Modified	Well Control:	Koomey Six Station 90 Gallon
Engine:	(2)Detroit 60 Series 475 HP	Annular:	11" 3M Shaffer
Mast:	Dreco 510	Pipe Rams:	11" 3M Shafco
Height:	133'	Manifold:	3 1/8" 35,000KPA
Max. Hook load:	157,460 daN 10 Lines	HCR:	Cammeron HCR
Substructure:	Edmonton Manufactures LTD	BOP:	
Max setback:	115,000 daN	Tubulars:	
Rotary/KB Beam to Ground:	5.02m	Collars:	18- 165mm 4.5" XH
Clear Working Height:	4.26m	Drill Pipe:	315- 101.6mm 4" FH X-95
Pumps:	(2)F-1000	HWDP:	60-101.6mm 4" FH
Engine:	(2) Cat C-27	Overhead:	
Mud System:	(2) Tank, 110 m3 usable fluid	Top Drive:	JH Electric 250 Ton, AC
Tank:		Hook/Block:	Gardner Denver 250 Ton
Shakers:	(2) Swaco Liner Motion	Drilling Line:	28.6 mm
Pumps:	2 Mission Magnum 6x5x11	Miscellaneous:	
Trip Tank:	3 m3	Water Tank:	63 m3
Pill tank:	4 m3	Fuel Tank:	28,000l storage
Suction Tank:	25 m3	Boiler:	80 HP Napanee
Settling Tank 1:	25 m3	Features:	Hydraulic Skate Catwalk, Rig Smart Crown Saver, BOP Lifting System.
Settling Tank 2:	30 m3	Rig Loads:	
Shaker Tank:	30 m3	Rig:	24
Agitators:	3- SOS Euro Drive	Boiler:	1
Gen Sets:	(2) Stanford 350 KW	Loader TP Shack & Misc.	3
Engine:	(2)Detroit 60 Series 625HP	Racking Capability:	4000 + M
Panel:	MCC		