



Rig 20- 5000m Cantilever Triple Electric

Drawworks:	Superior 750 UE	Well Control:	KoomeySix Station 100 Gallon
Engine:	Toshiba 1000 Amp DC	Annular:	11" 5M Shaffer
Mast:	Dreco 550	Pipe Rams:	11" 5M Shafco
Height:	131'	Manifold:	3 1/8" 35,000KPA
Max. Hook load:	180,000 daN 10 Lines	HCR:	Cammeron HCR
Substructure:	Dreco Self Raising	BOP:	
Max setback:	140,000 daN	Tubulars:	
Rotary/KB Beam to Ground:	5.48 m	Collars:	18- 165mm 4.5" XH
Clear Working Height:	4.89 m	Drill Pipe:	415- 101.6mm 4" FH X-95
Pumps:	(2)F-1600	HWDP:	60-101.6mm 4" FH
Engine:	(2) each, GE 752, 1000 Amp	Overhead:	
Mud System:	(2) 140 m3 usable fluid	Top Drive:	JH Electric, 350 Ton, AC Drive
Tank:		Hook/Block:	Gardner Denver 250 Ton
Shakers:	Derrick Flow Line	Drilling Line:	28.6 mm
Pumps:	2 Mission Magnum 6x5x11	Miscellaneous:	
Trip Tank:	3 m3	Water Tank:	55 m3
Pill tank:	7 m3	Fuel Tank:	TC-44 fuel tank, 30,000l storage
Suction Tank:	30m3	Boiler:	125 HP Volcano
Settling Tank 1:	30m3	Features:	Hydraulic Skate Catwalk, Rig Smart Crown Saver, BOP Lifting System, Baylor Brake, Self Elevating Sub.
Settling Tank 2:	30m3	Rig Loads:	
Shaker Tank:	30m3	Rig:	36
Agitators:	3- SOS Euro Drive	Boiler:	1
Gen Sets:	(2) Kato 1225 KW, (1) 800 KW	Loader TP Shack & Misc.	3
Engine:	(2) Cat 3512's, (1) Cat C-27	Racking Capability:	5000 + M
Panel:	CPS, Four bay SCR, Allen Bradely PLC		